

**B-FLEX**  
HEAT TRANSFER VINYL

ALEX

58

**B-FLEX ITALIA S.r.l.**

Via 1° Maggio, 44  
36050 Sovizzo (VI) ITALY  
Ph +39 0444.028139  
info@b-flexitalia.com

[www.b-flexitalia.com](http://www.b-flexitalia.com)

follow us on   

BF SUBLISTOP



# BF SUBLISTOP

## PRODUCT DESCRIPTION

BF SUBLISTOP was created to be applied on garments printed with dye sublimation. It comes with a built-in barrier to prevent the migration of pigments, keeping the material's original color unaltered even after multiple wash cycles.

This product is easy to work with; the sticky polyester carrier allows for fast weeding and easy repositioning of details that might have accidentally been removed. It is also soft and comfortable to wear, even with bulky designs.

Because of its 120-micron thickness, BF SUBLISTOP is soft on any fabric.

BF SUBLISTOP can be layered with itself or other B-FLEX films.

## APPLICATION INSTRUCTIONS

- Mirror cut BF SUBLISTOP with a 45° blade
- Weed BF SUBLISTOP and remove all excess material.
- Pre-heat your press to 140°C.
- Place the garment on the lower platen of your heat press.
- Press at 140°C for 10 seconds.
- Peel the carrier

## STANDARD SIZES

- H 150 cm => available lengths:  
25 mt (upon request)
- H 100 cm => available lengths:  
25 mt (upon request)
- H 75 cm => available lengths:  
25 mt (upon request)
- H 50 cm => available lengths:  
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

## APPLICATION TIPS

- Recommended Fibers: organic, synthetic, mixed
- Not recommended for layering.
- Can be applied with other B-FLEX films (ex. FATTY, GLITTER, FLOCK, etc.)
- Ability to cut designs as small as 0.5 cm
- Doesn't require a Teflon sheet during the pressing phase.

## TECHNICAL DATA

Film:	PU/ Polyurethane
Thickness:	120 μ (±5%)
Carrier:	Adhesive PET

## APPLICATION

Temperature:	140°C - 285° F
Time:	10"
Pressure:	medium – 3,5 bar – 50 PSI

## LINER REMOVAL

Hot

## WASH RESISTANCE

First Wash:	12 hours after application
Max. Wash temperature:	40° C
Dry Clean:	NO
Softener:	NO
Bleach:	NO
Dryer:	NO

## SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:  
BF SUBLISTOP. Rev\_2019/09.